





GL401 Series 🚥

13 gauge nylon liner

Tear and abrasion resistant

Low particulate shed

Grips well without being sticky

Offers tactile sensitivity and dexterity

Sizes Part No. GL401 • S, M, L, XL, 2XL

Sizing

The color of the binding around the cuff indicates the glove size.











2X-Large (11)

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Materials

Coating: polyurethane (PU) Liner shell: 13 gauge nylon Cuff: nylon & latex elastic

Country of Origin: China

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex

Do not use any chemicals or sharp-edged objects for cleaning the gloves. Cleaning can alter the

Cleaning

Wash in warm water (30-40°C) (86-104°F) Use mild detergent

performance levels of the glove.

Short cycle time (5-10 minutes) Low Tumble dry (60°C max) (140°F max)



Standards

CE EN388 standard features abrasion, cut, tear and puncture ratings. Abrasion ratings are based on the number of cycles required to abrade through the sample glove. Cut ratings are based on the number of cycles required to cut through the sample at a constant speed. Tear ratings are based on the amount of force required to tear the sample. Puncture ratings are based on the amount of force required to pierce the sample with a standard-sized point.

Testing Performance

EN388: 2003					
Abrasion (8,070)	1	2	3	4	
Cut	1	2	3	4	5
Tear	1	2	3	4	
Puncture	1	2	3	4	

There's more to see at **PYRAMEXSAFETY.COM**